


DIRIX RE

PANEL REDONDO DE EMBUTIR

INFORMACIÓN TÉCNICA



Modelo	SCL-PL-6W-RE	SCL-PL-12W-RE	SCL-PL-18W-RE	SCL-PL-24W-RE
Potencia	6W	12W	18W	24W
Flujo luminoso	300 lm	840 lm	1440 lm	2040 lm
Eficiencia	50 lm/W	70 lm/W	80 lm/W	85 lm/W
Tensión	220V~	220V~	220V~	220V~
Frecuencia	50 Hz	50 Hz	50 Hz	50 Hz
Corriente	50 mA	80 mA	130 mA	170 mA
Factor de potencia	>0,5	>0,5	>0,5	>0,5
Clase	II	II	II	II
Ahorro	90%	90%	90%	90%
Vida útil	30.000 hs	30.000 hs	30.000 hs	30.000 hs
Temp. de operación	-10 °C a + 50 °C	-10 °C a + 50 °C	-10 °C a + 50 °C	-10 °C a + 50 °C
Índice de protección	IP20	IP20	IP20	IP20
Ángulo de apertura	120°	120°	120°	120°
IRC/CRI	>80	>80	>80	>80
Atenuable	No	No	No	No
Medidas	A: 118,5mm B: 25mm	A: 168mm B: 25mm	A: 219mm B: 25mm	A: 294mm B: 25mm
Material	PVC reforzado	PVC reforzado	PVC reforzado	PVC reforzado
Color	Blanco/Negro	Blanco/Negro	Blanco/Negro	Blanco/Negro
Garantía	3 años	3 años	3 años	3 años